



cod.	Ø	pz/pcs	C	ØG	sp	R	bullone	cusc	binario	portata
400.40	40	12	16	Ø33	12	4,5	M8x30	1	-	60 kg.
400.50	50	12	16	Ø40	13	4,5	M8x30	1	-	80 kg.
400.60/10	60/10	12	24	Ø48	17	5,3	M10x45	1	-	100 kg.
400.60/16	60/16	12	24	Ø48	17	8,3	M10x45	1	902-904.16	100 kg.
400.70/16	70/16	6	33	Ø54	20	8,3	M14x70	1	902-904.16	190 kg.
400.80/16	80/16	6	33	Ø64	20	8,3	M14x70	1	902-904.16	200 kg.
400.80/20	80/20	6	33	Ø59	24	10,3	M14x70	1	902-904.20	200 kg.
400.90/16	90/16	6	33	Ø74	21	8,3	M14x70	1	902-904.20	210 kg.
400.90/20	90/20	6	33	Ø69	24	10,3	M14x70	1	902-904.20	210 kg.
400.100/16	100/16	6	33	Ø84	21	8,3	M14x70	1	902-904.16	230 kg.
400.100/20	100/20	6	33	Ø79	24	10,3	M14x70	1	902-904.20	230 kg.
400.120	120	4	33	Ø99	24	10,3	M14x70	1	902-904.20	250 kg.
400.140	140	4	43	Ø117	24	10,3	M16x70	1	902-904.20	280 kg.
400.160	160	2	43	Ø137	25	10,3	M16x70	1	902-904.20	300 kg.
400.200	200	2	43	Ø177	25	10,3	M16x70	1	902-904.20	340 kg.



Sliding gates accessories



Galvanized steel components



- Components to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

