



cod.	Ø	pz/pcs	C	ØG	sp	bullone	cusc	portata	Binario
402IX.60	60	6	24	Ø46	17	M10x45	1	100 kg.	
402IX.80	80	6	33	Ø62	20	M14x70	1	200 kg.	906IX
402IX.90	90	6	33	Ø72	21	M14x70	1	210 kg.	906IX
402IX.100	100	6	33	Ø82	21	M14x70	1	230 kg.	906IX
402IX.120	120	4	33	Ø100	24	M14x70	1	250 kg.	906IX
402IX.140	140	4	43	Ø118	25	M16x70	1	280 kg.	906IX



Stainless steel - Sliding gates accessorie



Stainless steel components



- Components to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

