



cod.	Ø	pz/pcs	C	ØG	sp	bullone	cusc	binario	portata
407.100x40	100 Tub. 40	6	33	Ø77	28	M14x70	2	906	410 kg.
407.100x50	100 Tub. 50	6	43	Ø77	28	M14x70	2	906	410 kg.
407.120x40	120 Tub. 40	6	33	Ø97	28	M14x70	2	906	430 kg.
407.120x50	120 Tub. 50	6	43	Ø97	28	M14x70	2	906	430 kg.
407.140	140 Tub. 50	4	43	Ø117	32	M16x70	2	906	550 kg.
407.160	160 Tub. 50	2	43	Ø137	32	M16x70	2	906	570 kg.
407.200	200 Tub. 50	2	43	Ø177	32	M16x70	2	906	600 kg.



Sliding gates accessories



Galvanized steel components



- Components to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.  
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

