



cod.	Ø	pz/pcs	A	B	C	ØG	I	asole	sp	R	cusc
410.60/10	60/10	12	80	36	24	Ø48	60	6,5x10	17	5,3	1
410.60/16	60/16	12	80	36	24	Ø48	60	6,5x10	17	8,3	1
410.80/16	80/16	6	120	48	37	Ø64	90	8,5x12	24	8,3	1
410.80/20	80/20	6	120	48	37	Ø59	90	8,5x12	24	10,3	1
410.100/16	100/16	6	120	56	38	Ø84	90	8,5x12	24	8,3	1
410.100/20	100/20	6	120	56	38	Ø79	90	8,5x12	24	10,3	1
410DC.80	80/DC	6	120	48	37	Ø59	90	8,5x12	24	10,3	2
410DC.100	100/DC	6	120	56	38	Ø77	90	8,5x12	28	10,3	2

cod.	binario	portata	CodTek
410.60/10	-	100 kg.	ARU041001ZB
410.60/16	902-904.16	100 kg.	ARU041008ZB
410.80/16	902-904.16	200 kg.	ARU041002ZB
410.80/20	902-904.20	200 kg.	ARU041003ZB
410.100/16	902-904.16	230 kg.	ARU041004ZB
410.100/20	902-904.20	230 kg.	ARU041005ZB
410DC.80	902-904.20	300 kg.	-
410DC.100	902-904.20	410 kg.	ARU041006ZB



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

