


## art. 412

## Wheel V groove 1 bearing with outside support





| cod.      | Ø      | pz/pcs | Α   | В  | С  | ØG  | ı  | asole  | sp | cusc | binario | portata |
|-----------|--------|--------|-----|----|----|-----|----|--------|----|------|---------|---------|
| 412.60    | 60     | 12     | 80  | 36 | 24 | Ø46 | 60 | 6,5x10 | 17 | 1    | -       | 100 kg. |
| 412.80    | 80     | 6      | 120 | 48 | 37 | Ø62 | 90 | 8,5x12 | 24 | 1    | 906     | 200 kg. |
| 412.100   | 100    | 6      | 120 | 56 | 38 | Ø82 | 90 | 8,5x12 | 24 | 1    | 906     | 230 kg. |
| 412DC.100 | 100/DC | 6      | 120 | 56 | 38 | Ø77 | 90 | 8,5x12 | 28 | 2    | 906     | 410 kg. |



Sliding gates accessories



Galvanized steel components



- · Components to weld and to fix
- · Adequately strengthen the areas anchoring the door and/ or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional per-



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressively authorized by the company will be prosecuted.



## art. 412

Wheel V groove 1 bearing with outside support

