



cod.	Ø	pz/pcs	A	B	C	D	ØG	sp	R	cusc	binario	portata
415.60/10	60/10	12	62	21	24	51	Ø48	17	5,3	1	-	100 kg.
415.60/16	60/16	12	62	21	24	51	Ø48	17	8,3	1	902-904.16	100 kg.
415.70/16	70/16	6	80	19	33	54	Ø54	20	8,3	1	902-904.16	190 kg.
415.80/16	80/16	6	80	19	33	59	Ø64	20	8,3	1	902-904.16	200 kg.
415.80/20	80/20	6	80	19	33	59	Ø59	24	10,3	1	902-904.20	200 kg.
415.90/16	90/16	6	100	28,5	33	72,5	Ø74	21	8,3	1	902-904.16	210 kg.
415.90/20	90/20	6	100	28,5	33	72,5	Ø69	24	10,3	1	902-904.20	210 kg.
415.100/16	100/16	6	100	28,5	33	78,5	Ø84	21	8,3	1	902-904.16	230 kg.
415.100/20	100/20	6	100	28,5	33	78,5	Ø79	24	10,3	1	902-904.20	230 kg.
415.120	120	6	120	38	33	98	Ø99	24	10,3	1	902-904.20	250 kg.
415.140	140	4	140	48,5	33	118,5	Ø117	24	10,3	1	902-904.20	280 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Araldo's property. All uses not expressly authorized by the company will be prosecuted.

