



cod.	Ø	pz/pcs	A	B	C	D	ØG	L	sp	cusc	binario	portata
416.60	60	12	62	21	24	51	Ø44	4	17	1	-	100 kg.
416.70	70	6	80	19	33	54	Ø50	4	20	1	906	190 kg.
416.80	80	6	80	19	33	59	Ø60	4	20	1	906	200 kg.
416.90	90	6	100	28,5	33	72,5	Ø70	4	21	1	906	210 kg.
416.100	100	6	100	28,5	33	78,5	Ø80	4	21	1	906	230 kg.
416.120	120	6	120	38	33	98	Ø98	4	24	1	906	250 kg.
416.140	140	4	140	48,5	33	118,5	Ø116	4	24	1	906	280 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

