



cod.	Ø	pz/pcs	A	B	C	D	ØG	sp	cusc	binario	portata
417.60	60	12	62	21	24	51	Ø46	17	1	-	100 kg.
417.70	70	6	80	19	33	54	Ø52	20	1	906	190 kg.
417.80	80	6	80	19	33	59	Ø62	20	1	906	200 kg.
417.90	90	6	100	28,5	33	72,5	Ø72	21	1	906	210 kg.
417.100	100	6	100	28,5	33	78,5	Ø82	21	1	906	230 kg.
417.120	120	6	120	38	33	98	Ø100	24	1	906	250 kg.
417.140	140	4	140	48,5	33	118,5	Ø118	24	1	906	280 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.  
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

