



cod.	Ø	pz/pcs	A	B	C	D	ØF	I	H	ØG	L	sp	cusc	binario	portata
426.60	60	12	110	7	24	15	Ø7	90	36	Ø44	4	17	1	-	100 kg.
426.70	70	6	135	7	33	17	Ø9	110	44	Ø50	4	20	1	906	190 kg.
426.80	80	6	135	12	33	17	Ø9	110	49	Ø60	4	20	1	906	200 kg.
426.90	90	6	155	9	33	18	Ø9	130	61	Ø70	4	21	1	906	210 kg.
426.100	100	6	155	14	33	18	Ø9	130	66	Ø80	4	21	1	906	230 kg.
426.120	120	6	185	14	32	20	Ø9	155	84	Ø98	4	24	1	906	250 kg.
426.140	140	4	205	15	32	22	Ø11	175	100	Ø116	4	24	1	906	280 kg.
426.160	160	2	225	20	37	24	Ø11	195	113	Ø136	4	25	1	906	300 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.  
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Araldo's property. All uses not expressly authorized by the company will be prosecuted.

