



cod.	Ø	pz/pcs	A	B	C	D	ØF	I	H	ØG	sp	cusc	binario	portata
432.90	90	6	155	9	33	18	Ø9	130	61	Ø70	24	2	906	390 kg.
432.100	100	6	155	14	33	18	Ø9	130	66	Ø77	24	2	906	410 kg.
432.120	120	4	185	14	37	20	Ø9	155	84	Ø97	28	2	906	430 kg.
432.140	140	4	205	15	42	22	Ø11	175	100	Ø117	32	2	906	550 kg.
432.160	160	4	225	20	42	24	Ø11	195	113	Ø137	32	2	906	630 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

