



cod.	Ø	pz/pcs	C	E	ØG	L	sp	CH	K	bullone	cusc	binario	portata
436.100	100	4	33	43	Ø80	4	24	Es.27	8	M18x60	1	906	380 kg.
436.120	120	4	33	43	Ø98	4	24	Es.27	8	M18x60	1	906	400 kg.
436.140	140	4	43	53	Ø116	4	25	Es.30	9	M20x70	1	906	670 kg.
436.160	160	2	43	53	Ø136	4	25	Es.30	9	M20x70	1	906	700 kg.
436.200	200	2	43	53	Ø176	4	25	Es.30	9	M20x70	1	906	750 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Lubricate all parts in contact with grease (every 6 months) .  
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

