




cod.	Ø	pz/pcs	C	E	ØG	sp	R	CH	K	bullone	cusc	binario	portata	CodTek
440.100	100	4	33	43	Ø77	28	10,3	Es.27	8	M18x60	2	902.20	560 kg.	ARU044005ZB
440.120	120	4	33	43	Ø97	28	10,3	Es.27	8	M18x60	2	902.20	580 kg.	ARU044006ZB
440.140	140	4	43	53	Ø117	32	10,3	Es.30	9	M20x70	2	902.20	920 kg.	ARU044001ZB
440.140x80	140 Tub. 80	4	72	-	Ø117	32	10,3	Es.30	9	M20x90	2	902.20	920 kg.	ARU044007ZB
440.160	160	2	43	53	Ø137	32	10,3	Es.30	9	M20x70	2	902.20	940 kg.	ARU044002ZB
440.160x80	160 Tub. 80	2	72	-	Ø137	32	10,3	Es.30	9	M20x90	2	902.20	940 kg.	ARU044008ZB
440.200	200	2	43	53	Ø177	32	10,3	Es.30	9	M20x70	2	902.20	980 kg.	ARU044003ZB
440.200x80	200 Tub. 80	2	72	-	Ø177	32	10,3	Es.30	9	M20x90	2	902.20	980 kg.	ARU044009ZB
440.250	250	2	73	-	Ø227	48	11,3	Es.36	11	M24x100	2	-	1450 kg.	ARU044004ZB



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Lubricate all parts in contact with grease (every 6 months) .
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

