



cod.	Ø	pz/pcs	C	E	ØG	sp	CH	K	bullone	cusc	binario	portata
442.100	100	4	33	43	Ø77	28	Es.27	8	M18x60	2	906	560 kg.
442.120	120	4	33	43	Ø97	28	Es.27	8	M18x60	2	906	580 kg.
442.140	140	4	43	53	Ø117	32	Es.30	9	M20x70	2	906	920 kg.
442.140x80	140 Tub. 80	4	72	-	Ø117	32	Es.30	9	M20x90	2	906	920 kg.
442.160	160	2	43	53	Ø137	32	Es.30	9	M20x70	2	906	940 kg.
442.160x80	160 Tub. 80	2	72	-	Ø137	32	Es.30	9	M20x90	2	906	940 kg.
442.200	200	2	43	53	Ø177	32	Es.30	9	M20x70	2	906	980 kg.
442.200x80	200 Tub. 80	2	72	-	Ø177	32	Es.30	9	M20x90	2	906	980 kg.
442.250	250	1	73	-	Ø217	48	Es.36	11	M24x100	2	906	1450 kg.



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Lubricate all parts in contact with grease (every 6 months) .
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

