



cod.	mm.	pz/pcs	A	B	C	D	E	F	G	H	N asole	L	sp	I	Ød	M	N olive
462PL.P	PIC-COLA	4	43-86	93-156	149-197	110	54	155	160	40	13x53	220	3	80	13	M14	Ø30x40
462PL.M	MEDIA	4	47-90	89-151	149-197	110	54	155	160	40	13x53	220	3	80	13	M16	Ø40x45
462PL.G	GRAN-DE	2	49-91	110-195	200-243	150	74	285	280	56	13x63	350	4	180	13	M16	Ø40x60



Sliding gates accessories



Galvanized steel/nylon components



- Components to weld and to fix.
- The weld must be adequately sized to support the applied forces and with suitable electrode material.
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Ariedo's property. All uses not expressly authorized by the company will be prosecuted.