



art. 756NYIXM

Stainless steel sliding trolley with 4 nylon screened wheels/ bearings







cod.	mm.	pz/pcs	А	С	ØD	E	М	portata per cop- pia	cusc. schermati	Barcode	CodTek
756NYIX.M	MEDIO	6	95	22	Ø40	50	M12	200 kg.	si	8033039321480	ARU075602NYIX



Sliding gates accessories



Stainless steel/nylon components



- The capacity refers for a couple of trolleys.
- Component to use in combination with the track art. 920; to guarantee the capacity of the trolley, the track must be supported every 700 mm.
- Reinforce adequately the attack spots.



- Components to fix
- Adequately strengthen the areas anchoring the door and/ or structure / frame.



Check the product every 6/12 months.

In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice. All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressively authorized by the company will be prosecuted.



art. 756NYIXM

Stainless steel sliding trolley with 4 nylon screened wheels/ bearings

