



cod.	mm.	pz/pcs	L	portata kg.	CodTek
859AIX.400	400	5	400	1600	AAC085906IX
859AIX.500	500	5	500	1600	AAC085907IX
859AIX.530	530	5	530	1600	AAC085908IX
859AIX.600	600	5	600	1600	AAC085909IX
859AIX.700	700	5	700	1600	AAC085910IX



Swing gates accessories



Stainless steel components and pvc



The capacity indicated is only if the cable is installed at "U" correctly using the assembling bolt art. 859MIX.
As load it means the max strength that the leaf can generate towards the cable in case of break and/ or disjunction of the upper hinge.
Check that the bearing structure is suitable to the strength transmitted by the leaf.



Components to fix.
Check the capacity considering the applied strengths.



Every 6 months check the integrity of the product.
In case of lacerations and/or the wear of the cable, provide to replace the product.
In case of anomalies, prevent the usage of the installed product and make it checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

