



cod.	∅	pz/pcs	∅	L	sp.	Barcode	CodTek
904.16x6-sp3	16 - 6 m.	54	∅16	6000	3 mm.	-	ARU090407ZB
904.20x3-sp3	20 - 3 m.	54	∅20	3000	3 mm.	8033039314314	ARU090401ZB
904.20x3-sp4	20 - 3 m.	54	∅20	3000	4 mm.	8033039316998	ARU090403ZB
904.20x6-sp3	20 - 6 m.	54	∅20	6000	3 mm.	8033039314321	ARU090402ZB
904.20x6-sp4	20 - 6 m.	54	∅20	6000	4 mm.	8033039316981	ARU090404ZB



Sliding gates accessories



Galvanized steel components



• Use art.903 to join several tracks.



- Component to be cemented.
- Size the reinforced concrete foundation, check that it is adequate for the forces transmitted by the gate leaf.
- Prepare the track for the installation: insert and/or weld in the holes the suitable rods for reinforced concrete.
- Installation: position the track inside the concrete, check its horizontality by a level bubble and anchor it properly. Cover with a concrete casting.
- Before positioning the gate wait for the concrete to cure completely.



Check the product every 6/12 months.  
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

