



cod.	m.	pz/pcs	A	B	ØD	H	I	L	M	CodTek
3009.1	1	2	250	17	9 - NR 2	92	500	1000	M8	ARU300902ZB
3009.2	2	2	250	17	9 - NR 4	92	500	2000	M8	ARU300903ZB



Telescopic gate system



Galvanized steel



Installation instructions

Maximum permitted weight: 300 kg per single leaf.
The wheel and drive system must be installed so that the driven leaf is only pulled, not lifted or supported by the drive system.

The weight of the leaf must be correctly carried by the wheels and the lower guide track.

Check that:

- The leaves slide freely by hand, with the automation disconnected;
- There are no jams, rubbing points, jumps or hard spots;
- The leaves remain aligned and parallel along the entire travel;
- The tracks are straight, clean and free from obstacles;
- The sliding area is kept free from dirt, gravel, leaves or ice;
- The drive system works without jerks, misalignment or abnormal tensioning;
- The leaves are fitted with mechanical end stops in both opening and closing positions.

The correct operation and service life of the entire system also depend on proper adjustment of the automation. The gate movement must take place with:

- Speed suitable for sliding gates;
- Smooth start;
- Soft slowdown;
- Non-abrupt direction reversal;
- Force adjusted according to the applicable standards for motorized gates.

Excessive acceleration, hard braking or abrupt direction reversal may significantly reduce the service life of the entire system.

In case of irregular movement, abnormal noise, jerking or jamming, do not put the gate into service before the defect has been corrected.



- Components to weld and to fix.
- The weld must be adequately sized to support the applied forces and with suitable electrode material.
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.

In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.



